

BATEMAN



RB35

SPECIFICATIONS RB35

Dimensions (dependent upon specification)

Height	3.3m
Width	2.8m
Length	7.0m
Ground Clearance	0.96m (standard)
Wheel Base	3.3m
Turning Radius	4.8m
Weight	8970kg
Fuel Capacity	220 litres

Steering

Positive Link 2/4-wheel steer, fully hydraulic

Suspension

Hydraulic fully active front and rear

Wheel Track

Hydraulic adjustable axles with 18 inches variable track width

Engine and Transmission

John Deere 223hp 6-cylinder water-cooled Turbo-charged diesel
Fully Hydrostatic four wheel drive, variable from 0 up to 45kph
Hydrostatic and Dynamic braking. Parking brake manually operated or automatically applied when the engine is stopped.

Cab

Steel construction, with all round panoramic tinted glass
Rubber mounted suspension
Cladded and soundproofed
Carbon filtration
Automatic climate control system
Bluetooth CD/Radio player
Roof mounted 360 degree working lights, and warning beacon
Wash wipe windscreen wiper
Large extendable wing mirrors
Fresh water hand/tyowash
Pneumatically operated step
Air suspension seat with fore and aft movement
Raise, lower and tilt steering column
External airline pickup point

Sprayer

Tank, Stainless Steel	4000 litre fully baffled, Tank contains gauges with dry indicator
Boom	Bateman 12/20/24 metre Bateman Contour, Bateman 12/18/20/24 metre Bateman Contractor Contour, Both having 'Gull Wing' folding OR Bateman (M/G.) Variable Geometry up to 39m V.G. boom options 12/20/24m 12/24' to other 28-30-32' or 39m
Hling	4 cylinder 270 litre/min pump Stainless steel chemical hopper, can wash/bowl rinse, with twin venturis Self-fill or bowser quick fill
Controls	LH5000 (GPS enabled) Electric tapping system giving in-cab control of tank and sprayline rinse Auto priming system on all machines Pneumatic diaphragm line valves Ramsey box
Demounting	Full set of demount legs and jacks

Wheels

Row crops 14.9R34 or 16.9R30

Controls

Joystick Command arm forward / reverse and sprayline controls
Electro-hydraulic boom control
Hydraulic spool for pump engagement

Options

Triple nozzles with 3 sets of jets
Twin stainless steel spraylines with 2 sets of jets
Spreader skid unit, mudguards and demount jacks
Bateman Boutmarker
Low ground pressure tyres
Air assisted sleeve boom
400 litre/minute 6 cylinder spray pump
Twin spray pumps

We reserve the right to alter specifications without prior notice
Our policy is one of continuous development



BATEMAN ENGINEERING LIMITED

BYCOTT, CHULMLEIGH, DEVON EX18 7DS

Telephone: 01769 580439

Fax: 01769 581023

www.batemansprayers.com